



## Applications

- New Lifemaster tread provides aggressive traction without damaging sensitive working environments.
- Floatation even over new asphalt and concrete without scarring.

## Benefits

- Solid Construction.
- Easy to use.

## Specifications

OTT FITMENT GUIDE							OTT SPECIFICATIONS (maximum speed 25 km/h - 16 mph)								
TIRE SIZE	OTT SIZE	TREAD	WHEELBASE				TRACK WEIGHT		TRACK WIDTH		LUG HEIGHT		CARCASS THICKNESS		HORSEPOWER RANGE (hp) (min-max)
			Min		Max		lbs	kg	inch	mm	inch	mm	inch	mm	
			inch	mm	inch	mm									
10x16,5	10x25	TM or LM	28 1/2	724	31 1/4	794	267	121	13 <sup>1/5</sup>	335	1 <sup>1/4</sup>	32	1	25.4	35-85
	10x26	TM or LM	31 1/2	800	34 1/4	870	276	125							
	10x27	TM or LM	34 1/2	876	37 1/4	946	285	129							
	10x28	TM or LM	37 1/2	953	40 1/4	1022	294	133							
	10x29	TM or LM	40 1/2	1029	43 1/4	1099	302	137							

Treads: TM = Standard Trackmaster - LM = New Lifemaster



### The VECTRA OTT Track® Kit Includes:

- (1) VECTRA OTT Track Over the Tire Tracks
- (1) Full, 3/4, 1/2 Pitch Sections for Tensioning & proper fitment
- (4) Self-Locking Pins (durable, high tensile steel)
- (1) Pilot pin
- (1) Strap ratchet



### ATTACHMENTS FOR SKID STEER LOADERS

